



QuasIR™ 3000 Integrating Sphere FT-NIR

Portability without Compromise

- Compact and Portable
- High Performance
- Easy-to-use
- Suitable for the road, lab, or factory
- Low cost of ownership and maintenance
- Point-of-need
- Direct calibration transfer
- Rugged, insensitive to vibration
- Wide operating temperature range
- Flexible, easy-to-use software
- Large sampling area
- Instrument-to-instrument consistency

Versatility

The QuasIR™ 3000 offers a new kind of NIR analysis solution. Its portable design brings NIR directly to the point-of-need and its unmatched spectroscopic performance delivers the fastest, most accurate results.

Innovation

The QuasIR™ 3000 delivers a wide range of technical innovations including our PermAlign™ optics technology. This advanced optical design maintains alignment and performance under conditions from the routine to the extreme.

Our Advanced-ID™ software is a targeted screening software tool that allows quick screening and semi-quantitative results for concentrations substantially less than 0.1%. Advanced-ID™ extends the use of NIR to further reduce ingredients supply chain risk and protect brand integrity.

Large Sampling Design

The QuasIR™ 3000 has an enhanced 23mm sampling area, which is up to 5 times larger than competitive products. The large sampling area, with a scratch-resistant sapphire window, helps produce better, more reproducible results.



Consistency

The QuasIR™ 3000 is designed to ensure direct calibration transfer without the frustration of standardizing instruments or adjusting models to accommodate excessive instrument variability. Our technology and design ensure unmatched consistency and direct method transfer with no loss in performance, so you can expand your QuasIR™ fleet with confidence.

Key Applications:

Food Processing/Authentication



Feed Analysis



Tobacco Processing



Pharmaceuticals





QuasIR™ 3000 FT-NIR System Specifications

General Specification	Value	Alternate Value/Benefit
Dimensions (W x D x H)	44.0 x 24.1 x 14.5 cm	17.32 x 9.49 x 5.71 in.
Weight	< 8.85 kg	< 19.51 lbs.
Power Supply	12V / 3A Supply, 60W max	
Communication	USB	
Operating Temperature	0 - 40°C	32 - 104°F
Enclosure Protection	IP54 (dust)	
Sampling Mode	Diffuse Reflectance for solids, Transmission for liquids	Maximum signal and collection efficiency
Sampling Device	High performance gold-coated integrating sphere	Maximum signal and collection efficiency
Sampling Area	23 mm	Improved results
Automated Verification & Instrument Diagnostics	Automatic, internal, 4-position validation wheel	Continuous performance monitoring
Performance Specifications		
Wavelength Range	12,800 - 4,000 cm ⁻¹	785 - 2,500 nm
Spectral Resolution	Better than 4 cm ⁻¹	< 0.78 nm @ 1392 nm
Wavelength Accuracy	< 0.1 cm ⁻¹ @ 7181.68 cm ⁻¹	< 0.019 nm
Wavelength Repeatability	< 0.1 cm ⁻¹ @ 7181.68 cm ⁻¹	< 0.009 nm
Photometric Accuracy	Better than 0.1% T	
Signal-to-Noise Ratio	> 20,000:1	Excellent sensitivity
Noise	Better than 20 micro au	Low detection limit
Detector	TE cooled InGaAs	
Data Acquisition A/D converter	24-bit high speed Delta-Sigma	
Reliability Specifications		
Laser Life	> 10 years	Low downtime & ownership costs
NIR Source Life	> 20,000 hours, user replaceable	Low downtime & ownership costs
Desiccant	User Replaceable	Low ownership costs
Regulatory Compliance		
EMC directive 2004/108/EC	Complies	
RoHS directive 2002/95/EC	Exempt	
WEEE directive 2002/96/EC	Complies	

Document#: GS-DS-Q3000-1.2EN



Quantum Analytics is an authorized distributor for Galaxy Scientific. To inquire about Galaxy instruments and take advantage of our financing and value-added services, please contact Quantum Analytics today.
Email LQA@LQA.com or call 1-800-992-4199.